

ANNEALED COPPER TUBE - TYPE L POLY COATED (CTLG)

Applications: Type L (G / GAS) Poly Coated ASTM B88 / B837 Specification for Seamless Copper Tube. Suitable under CAN/CGA - B149-00 for Under Ground and Above Ground use in Natural Gas and Propane installations. Also suitable for use on RV'S and other Gas applications. Check local codes to ensure copper tube selection meets your application requirements.

LONGER COIL LENGTHS AVAILABLE UPON REQUEST.

Dash Size	L Size (Nominal)	Tube O.D. (IN.)	Wall Thickness (IN.)	Working Pressure (P.S.I.)*	Coil Length (FT.)
-6-60	1/4	3/8	.030	912	60
-6-100	1/4	3/8	.030	912	100
-6-250	1/4	3/8	.030	912	250
-8-60	3/8	1/2	.035	779	60
-8-100	3/8	1/2	.035	779	100
-8-250	3/8	1/2	.035	779	250
-10-60	1/2	5/8	.040	722	60
-10-100	1/2	5/8	.040	722	100
-10-250	1/2	5/8	.040	722	250
-12-60	5/8	3/4	.042	631	60
-12-100	5/8	3/4	.042	631	100
-14-100	3/4	7/8	.045	582	100

* Working Pressure Rated at +100°F, (+38°C)