

## FUEL LINE TUBE - POLYURETHANE (FLT)

**Applications:** This Ether based polyurethane tube has been specially formulated for use with gasoline and is also suitable for such applications as air transfer lines, granular transfer lines, lubrication lines and robotics control lines. It is clear with a blue tint to allow see-through convenience. Polyurethane tube features abrasion and cut resistance, good flex fatigue and resilience and excellent resistance to ozone, solvents and fuel. Items and colors not shown are subject to minimum runs.

- **PACKAGING:** 100 FT COILS
- **TEMPERATURE:** -40°F to +175°F, -40°C to +79°C
- **FITTINGS:** HOSE BARBS

ALSO SEE FUEL LINE HOSE.

Dash Size	Tube O.D. (IN.)	Actual I.D. (IN.)	Wall Thickness	Working Pressure P.S.I.
-42	1/4	1/8	1/16	100
-53	5/16	3/16	1/16	75
-64	3/8	1/4	1/16	60
-75	7/16	5/16	1/16	50
-86	1/2	3/8	1/16	45
-128	3/4	1/2	1/8	60

\* NOTE: WORKING PRESSURE RATED AT +75°F, +24°C. ANY AMBIENT OR INTERNAL INCREASE IN TEMPERATURE WILL LOWER THE WORKING PRESSURE.