

SNAPTITE "VH" (VALVED) Q.D. (QD-VH)

Applications: Hydrailic

- Fully engineered design meets or exceeds MIL-C-51234
- "Jet Stream" valve design for superior, smoother flow.
- Much more compact than standard hydraulic coupler sets.
- Wide variety of sizes and configurations.
- "VH" valved and "PH" non-valved are completely interchangeable for double, single or no shut-off.
- For non-valved couplers replace "V" in part number with "P"
- Example: QD-PHN6-6F
- For Brass prefix "V" in part number with "B" Example: BVHN6-6F
- For Stainless prefix "V" in part number with "S" Example: SVHN6-6F
- Proven by years of use in hydraulic-pneumatic applications handling a variety of gases and fluids.

WORKING PRESSURES (PSI)						
Valve and Valve (Double Shut-Off) Valve and Plain (Single Shut-Off)				Plain and Plain (No Shut-Off)		
Q.D. Size	Steel	Brass	Stainless Steel	Steel	Brass	Stainless Steel
1/4	6500	2250	5000	11000	4000	10000
3/8	4500	2250	4000	11000	4000	8000
1/2	4000	2000	3750	11000	4000	8000
3/4	3500	2000	2000	9000	3500	7000
1	2000	1750	2000	6000	3000	4000
1-1/4	1750	350	1500	5000	1000	3000
1-1/2	1500	350	1500	5000	1000	3000
2	1500	400	500	4000	750	1000
2-1/2	1000	400	400	1000	400	400
3	750	200	400	750	200	400