

SERIES A ISO 7241-1 PARKER 6600 INTERCHANGE Q.D. (QD-ISOA)

Applications: Hydraulic

- Interchangeable with Parker 6600 series, Aeroquip 5600 Series, Safeway S56 Series and other manufacturer's couplers and nipples built in accordance to I.S.O. 7241-1 Series "A".
- 4 to 1 Safety factor (Min. Burst = W.P. X 4)
- High Strength Steel Construction.
- Proven ball lock mechanism.
- Hydraulic applications where connection and disconnection is required either for maintenance or operation. For use on truck & trailer, snow plows, agricultural, dump, construction equipment.
- Temperature Range: -40F to 250F



COUPLER SET					
MAXIMUM WORKING PRESSURE (PSI)					
	1/4	3/8	1/2	3/4	1
STEEL	5000	4600	4000	4000	4000

VALVED COUPLER - STEEL

PART No.	Body Size	Female Pipe
QD-ISOAC4-4F	1/4	1/4
QD-ISOAC6-6F	3/8	3/8
QD-ISOAC8-8F	1/2	1/2
QD-ISOAC12-12F	3/4	3/4
QD-ISOAC16-16F	1	1

VALVED NIPPLE - STEEL

PART No.	Body Size	Female Pipe
QD-ISOAN4-4F	1/4	1/4
QD-ISOAN6-6F	3/8	3/8
QD-ISOAN8-8F	1/2	1/2
QD-ISOAN12-12F	3/4	3/4
QD-ISOAN16-16F	1	1