



BITE-FORCE Push-in fittings and valves are the new “no tools required” solution to connect CPVC, PEX and copper plumbing system in seconds.

Our completely lead-free system can be used for potable water, grey water and hydronic heating systems under floors and behind the walls in residential and commercial construction applications.

Connect BITE-FORCE fittings easily in tight spaces and rotate after assembly to desired orientation – no compression fitting leaks, or awkward and dangerous soldering required.

#### Features:

- 25 year limited warranty against defects in materials and workmanship.
- Certified by cUPC, IAPMO, ANSI/NSF to ANSI/NSF-61 and ASSE 1061 product standard for use in potable water and hydronic heating water distribution.
- Suitable for behind the wall installation where local plumbing code recommends and for use underground when completely wrapped in impermeable non-adhesive silicone tape.
- Maximum working pressure: 200 psi
- Maximum temperature: 200°F (93°C)
- Lead free brass
- EPDM O-Rings
- Removable pipe stiffeners

#### Pipe Size Compatibility / Pipe Insertion Depth

Dash Size	Nominal Size	Pipe / Tube O.D. (In.)	Pipe Insertion Depth (In. ±0.02)	Pipe Insertion Depth (mm ±0.5)
-6	1/4 CTS	3/8	0.654	16.6
-8	3/8 CTS	1/2	0.902	22.9
-10	1/2 CTS	5/8	0.953	24.2
-14	3/4 CTS	3/4	1.094	27.8
-18	1 CTS	1-1/8	1.295	32.9